

Constant level beeplast polypropylène trolley 50 kg



Short description:

PROVOST is offering this constant-level trolley as the perfect solution for your handling operations. The level of the shelf rises or lowers automatically to match the weight of the load being transported.

As a result, staff can load and unload without having to bend over repetitively. The height of the shelf is maintained thanks to a strong steel spring with 50 kg of power.

This trolley is not very bulky and is very light and manoeuvrable. The rising base and ergonomic design reduces the risk of injury. 3 options: without handle, with handle or with 2 handles.

Photo for information only.

Description:

- Material for the sides: Beeplast "honeycomb" polypropylene with a thickness of 6.5 mm, grey
- Aluminium metalwork, corners made from black injection-moulded plastic
- Base reinforced with a polypropylene sheet with a thickness of 8 mm.
- 4 castors with a rubber tyre and diameter of 80 mm, 2 of which swivel and 2 of which are fixed, in rectangular configuration.
- Pantograph system, 50 kg spring force, polypropylene shelf with thickness of 8 mm reaching 50 mm from the top of the trolley when empty
- External dimensions: 850 x 700 x 850 mm (L x H x D).
- Internal dimensions: 830 x 680 x 551 mm (L x H x D)

Advantages of "Beeplast" honeycomb polypropylene:

- Lightness - density: 2500 gr/m²
- Shock-proof and resistant to changes in temperature: between -20°C and +90°C (use between 0°C et 60°C)
- Very long lasting - 100% recyclable
- Resistant to water and most oils, grease and chemical products Chemically inert.
- Does not release harmful substances in case of fire. Low-flammability

Contact us

Réf.	Height (mm)	Length (mm)	Width (mm)	Model	Volume (l)	Weight (kg)	
------	-------------	-------------	------------	-------	------------	-------------	--

4059001511	850	850	700	1 handle	310	35	816.80 €
4059001512	850	850	700	2 handles	310	35	850.30 €
405900151	850	850	700	Without handle	310	35	783.30 €

Réf.	Désignation	0
------	-------------	---